

TODA Diesel K Semi Synthetic 10W-30

Product Descriptions

TODA Diesel K Semi Synthetic 10W-30 is a semi-synthetic heavy-duty diesel engine oil for high performance vehicle such as sport utility vehicle (SUV), 4 wheels drive and new pick-up truck. It is the highest quality in protection and bearing corrosion control technology with API CK-4 and additives such as anti-wear (protect engine), and soot reduction (clean engine).

Quality Attributes

- Enhanced oxidation stability
- Superior engine protection
- Extended oil changes
- Excellent anti-wear performance
- Lower oil consumption
- Excellent soot and viscosity control
- Longer engine life

Applications

- The latest heavy-duty diesel engines
- On-highway heavy-duty trucking and off-highway applications including trucking, mining, construction, agriculture and marine

Specifications

API CK-4

ACEA E9-12

CAT ECF-3

Cummins CES 20086

Detroit Diesel DDC93K222

Deutz DQC III-10 LA

Ford WSS-W2C171-F

JASO DH-2

Mack EOS-4.5

MAN 3275, 3575

MB 228.31

MTU 2.1

Renault VI RLD-4

Volvo VDS 4.5

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail: sales@todaoiljapan.com

Typicals

Density @15 °C, kg/l	0.87
Viscosity @40 °C mm ² /s	80.5
Viscosity @100 °C mm ² /s	12
Viscosity Index	143
Pour Point, °C	-40
Flash Point COC, °C	220
Total Base Number, mgKOH/g	10.1

Packing Size 1 liter, 6 liters, 18 liters, 200 liters

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail sales@todaoiljapan.com