

TODA 4T BL

Product Descriptions

TODA 4T BL is a general performance four-stroke motorcycle engine oil intended for lubrication of small four-stroke engines. Manufactured from high quality mineral base oils and additives at the highest level. To prevent wear and corrosion of the engine.

Quality Attributes

- Extended engine life
- Effective wear protection
- Enhanced cleanliness prevents sludge and engine deposit formation.
- Thermal and oxidation stability, deposit control
- Good corrosion protection

Applications

- Suitable for use in 4-Stroke motorcycle engines where API SL and JASO MB performance levels are recommended.

Specifications

API SL

JASO MB

Typicals

SAE Grade Viscosity	10W-30	10W-40	20W-40
Density @15 °C, kg/l	0.87	0.88	0.89
Viscosity @40 °C mm ² /s	69	88	122
Viscosity @100 °C mm ² /s	10.7	12.7	15
Viscosity Index	144	141	126
Pour Point, °C	-35	-33	-30
Flash Point COC, °C	220	225	230

Packing Size 0.8 liters, 1 liter

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail sales@todaoiljapan.com