

TODA 2T

Product Descriptions

TODA 2T is a general performance two-stroke engine oil. It's manufactured from highest quality mineral base oils and additives to prevent wear and corrosion of the engine.

Quality Attributes

- Air and liquid-cooled two-stroke engines
- Excellent cylinder and bearing lubrication
- Particularly suitable for Japanese high performance engines
- Prevents piston ring sticking
- Improved anti-rust and corrosion protection
- Air-cooled, oil-gasoline premix engines at manufacturers' recommended gasoline-to-oil ratios, up to 50:1
- Reduced exhaust system blockage
- Reduced spark plug fouling and deposit induced preignition

Applications

- Suitable for use in 2-Stroke engines where JASO FC, API-TC, ISO EGC & EGD MA performance levels are recommended

Specifications

API-TC

ISO EGC & EGD

JASO FC

Typicals

Density @15 °C, kg/l	0.87
Viscosity @40 °C mm ² /s	67.3
Viscosity @100 °C mm ² /s	9.2
Viscosity Index	112
Pour Point, °C	-9
Flash Point COC, °C	150
Total Base Number, mgKOH/g	0.9

Packing Size 0.5 liters, 1 liter

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail: sales@todaoiljapan.com