

TODA ATF 1A LV

Product Descriptions

TODA ATF 1A LV Fully Synthetic is a 100% synthetic gear oil for the new generation of automatic transmission. It is best used in new model vehicles made from North America, Asia and Europe and has high efficiency, smooth transmission, high pressure, and excellent wear protection with long service life time value.

Quality Attributes

- Provides consistent shift performance
- Excellent oxidation stability
- Protects against rust and corrosion
- Excellent EP and anti-wear performance
- Excellent anti-shudder durability performance

Applications

- Multi-functional Long life ATF for modern, electronically-controlled automatic transmissions in cars and vans
- Suitable for use in power steering systems.

Specifications

Aisin Warner JWS 3324 (WS), AW-1	Audi/VW G 060 162 (ZF Lifeguardfluid 8) (ZF No. S671 090 312)
Audi/VW G 055 540 (A2)	BMW MINI 83 22 0 397 114/163 514
Ford Mercon LV, Mercon SP	GM/GMC/Opel/Saturn AW1
GM/GMC/Opel/Saturn 88863400	GM/GMC/Opel/Saturn 88863401
GM Dexron VI	Honda DW-1
Hyundai/Kia SP-IV	Hyundai/Kia SP-IV M (SP4-M)
Hyundai/Kia SP-IV-RR	Hyundai/Kia NWS 9638
JASO M315-2013 1A-LV	KIA ATF SP-IV, SP-IVM
Mazda ATF FZ	Mercedes Benz MB 236.41
Mitsubishi Diaqueen J3	Mitsubishi Diaqueen ATF PA
Nissan Matic Fluid S	Saab 93 165 147
Shell L 12108	Toyota ATF WS
VW G-055-540 (A2)	VW G 060 162 (ZF Lifeguardfluid 8)
ZF Lifeguardfluid 9	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail: sales@todaoiljapan.com

Typicals

Density @15 °C, kg/l	0.86
Viscosity @40 °C mm ² /s	28
Viscosity @100 °C mm ² /s	5.95
Viscosity Index	165
Pour Point, °C	-46
Flash Point COC, °C	185
Colour	Red

Packing Size 1 liter, 5 liters, 18 liters, 200 liters

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail sales@todaoiljapan.com