

TODA T3

Product Descriptions

TODA T3 are high performance monograde diesel and gasoline engine oils formulated from advanced technology base oils and a balanced additive system. TODA T3 provides excellent protection in applications where a monograde diesel and gasoline engine oil is required.

Quality Attributes

- Excellent protection against ring sticking
- Protection against wear and deposits
- Controls formation of acids when using higher sulphur fuels
- Prolonged engine life

Applications

- Suitable for petrol and diesel engines, both with and without turbochargers, under all operating conditions.

Specifications

API CF/SF

Typicals

SAE Grade Viscosity	30	40	50
Density @15 °C, kg/l	0.89	0.89	0.89
Viscosity @40 °C mm ² /s	101	133	212
Viscosity @100 °C mm ² /s	11.7	14.2	19.5
Viscosity Index	101	101	101
Pour Point, °C	-18	-15	-15
Flash Point COC, °C	239	244	255
Total Base Number, mgKOH/g	6.5	6.5	6.5

Packing Size 1 liter, 5 liters, 18 liters, 200 liters

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Toda Oil Japan 15/9 Buddhamonthon Sai 2 Rd., Taweewattana Bangkok 10170, Phone: Sales +66 (80)515-2424

Website: www.todaoiljapan.com E-mail sales@todaoiljapan.com