

TODA MT Car&Pickup Fully Synthetic

Product Descriptions

TODA MT Car & Pickup Fully Synthetic is an extreme pressure fully synthetic gear oil. TODA MT Car & Pickup Fully Synthetic is suitable for manual gearboxes, transfer cases and transaxles in passenger cars, 4WDs and pickup trucks that specify the use of SAE 75W-85, 75W-90 oils

Quality Attributes

- Excellent Anti-Wear and Extreme-Pressure Properties
- Compatible with normal mineral oil, hence no special flushing procedure is needed when changing from mineral to synthetic
- Compatible with many elastomers and other sealant materials.
- Superior shear stability and reduced oxidation
- Outstanding Low Temperature Performance and High Temperature Oxidation Stability

Applications

Recommended for manual gearboxes, transfer cases and Transaxles in passenger cars, light commercials, 4WDs, trucks, construction, earthmoving and agricultural equipment that specify the use of an API GL-4

Specifications

API GL-4

Typicals		
SAE Grade Viscosity	75W-85	75W-90
Density @15 °C, kg/l	0.86	0.86
Viscosity @40 °C mm²/s	65.2	98
Viscosity @100 °C mm²/s	12.1	16.4
Viscosity Index	184	180
Pour Point, °C	-45	-50
Flash Point COC, °C	220	230

Packing Size 1 liter, 5 liters, 18 liters, 200 liters

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.